




GALATEA MW SL™

640 x 512 - 15μm

THE NEW GALATEA MW SL™ product is particularly suitable for integration into small UAV gimbals featuring high MTTF and compactness.

THE FIRST **SWAP** DETECTOR WITHIN THE **PLUGUP** PLATFORM



HIGH IMAGE QUALITY



LOW POWER CONSUMPTION



COMPACTNESS



EASY MECHANICAL INTEGRATION



DEFENSE

FIXED
SURVEILLANCE





MULTI-PURPOSE



LOW POWER





COMPACT



WEIGHT



LOW ACOUSTIC NOISE



LYNRED HEADQUARTERS DEVELOPMENT & PRODUCTION CENTER

Actipole - CS 10021 - 364, route de Valence
38113 Veurey-Voroize - France
Phone +33 (0)4 76 28 77 00
info@lynred.com

LYNRED ASIA PACIFIC PTE LTD

5 Shenton Way,
#22-04 UIC Building
068808 Singapore
info@lynred.com

LYNRED USA

373 US Highway 46W
Fairfield, NJ 07004, USA
Phone +1 973.882.0211
info@lynred-usa.com

NIT (New Imaging Technologies) Premium SWIR by LYNRED

1 impasse de la Noisette
91370 Verrières-le-Buisson - France
Phone +33 1 64 47 88 58
info@new-imaging-technologies.com

THE FIRST SWAP DETECTOR WITHIN THE PLUGUP PLATFORM

PRODUCT EMBEDDED FEATURES

IDDCA + PROXIMITY BOARD + CRYOCOOLER CONTROLLER

ARRAY FEATURES

Detector spectral response ■ 3.6 to 4.2μm

FPA operating temperature ■ Up to 150 K

ROIC (READ-OUT INTEGRATED CIRCUIT)

Selection ■ IWR and ITR

ROIC architecture ■ Direct Injection

ROIC functionalities ■ Invert/Revert

Windowing modes ■ Down to 160 x 2

Charge handling capacity ■ 2.1 Me-

Signal output rate ■ 10 MHz

Frame rate ■ 60 Hz

TYPICAL* PERFORMANCES

NETD ■ < 28 mK (27°C, 50%WF, f/4)

Array operability ■ > 99.5%

RFPN at 50% well fill ■ < 0.5 × RMS noise

INTERFACES

Video output ■ CameraLink® Base Mode

Communication ■ CameraLink® UART

Product Power Supply ■ 12 Vdc typical

PHYSICAL CHARACTERISTICS

Maximum Outline dimensions (LxWxH) ■ 56 mm x 77 mm x 72.5 mm

Weight ■ 360 g

K588

Aperture ■ f/4; f/5.5

Regulated Input power @20°C ■ 3Wdc

Cooldown Input power @20°C ■ 12Wdc


Cooldown time @20°C ■ 3min 30s

Cooler MTTF ■ 32,000hrs

AVAILABLE SERVICES

Technical training and support

Recognition distances for human measuring 1.80 m x 0.50 m



Range for Johnson's criteria, target deltaT = 2 K, perfect atmospheric and optics transmissions, theoretical square pixel.