# ATI GALATEA MW SL

640 x 512 - 15µm

**OPENING THE PLUGUP FAMILY TO STATE-OF-THE-ART IMAGE CORRECTION** 

The ATI GALATEA SLTM Advanced Thermal Imager

is a SWaP module that streamlines camera development for diverse applications such as UxS (Unmanned systems) and surveillance.

The ATI GALATEA SLTM

incorporates a proven, high performance LYNRED thermal sensor combined with advanced image algorithms, ensuring the delivery of high-quality thermal images.















# OPENING THE PLUGUP FAMILY TO STATE-OF-THE-ART IMAGE CORRECTION















POWER COMPACT

HIGH
PERFORMANCE
<b>ALGORITHMS</b>

LOW POWER CONSUMPTION

#### PRODUCT EMBEDDED FEATURES

IDDCA + PROXIMITY BOARD + CRYOCOOLER CONTROLER + ATI BOARD

ARRAY FEATURE	S
---------------	---

Detector spectral response	■ 3.6 to 4.2µm
FPA operating temperature	Up to 150 K

#### **ROIC (READ-OUT INTEGRATED CIRCUIT)**

Selection	IWR and ITR
Windowing modes	■ TBD
Charge handling capacity	■ 2.1 Me-
Signal output rate	■ 10 MHz
Frame rate	up to 60 Hz

#### PERFORMANCES

NETD Sensor	< 28 mK (27°C, 50%WF, f/4)
NETD Post Process	<20 mK
Array operability	<b>&gt;</b> > 99.5%
RFPN at 50% well fill	< 0.5 × RMS noise
Aperture	■ f/4; f/5.5
Lag Time	■ 1 Frame

#### INTERFACES

Video output	■ CameraLink®, USB3
Product Power Supply	■ 12 Vdc typical
Connector	SAMTEC LSHM-140-025-L- DV-A-S-K

### PHYSICAL CHARACTERISTICS

Maximum Outline dimensions (LxWxH)	■ 58.5 mm x 77 mm x 72.5 mm
Weight	■ 375 g
K588	

K588	
Regulated Input power @20°C	■ 4Wdc
Cooldown Input power @20°C	■ 12Wdc
Cooldown time @20°C	■ 3mim 30s
Cooler MTTF	■ 32,000hrs

#### **EMBEDDED ALGORITHMS ONTO FINAL PRODUCT**

#### ALGORITHMS

- 2 point Non-Uniformity Correction (up to 4 tables)
- Bad Pixel Replacement
- Denoising (Spatial & Temporal)
- Evolutive Bad Pixel Detection
- Image Flip (H/V)
- Video Test Pattern
- Destripping
- Tone Mapping
- Digital Detail Enhancement
- Graphic Overlay

#### **AVAILABLE SERVICES**

Technical training and support

LYNRED Toolbox™ (LTB)







LYNRED HEADQUARTERS
DEVELOPMENT & PRODUCTION CENTER

Actipole - CS 10021 - 364, route de Valence 38113 Veurey-Voroize - France

info@lynred.com

## LYNRED ASIA PACIFIC PTE LTD

5 Shenton Way, #22-04 UIC Building 068808 Singapore info@lynred.com

#### LYNRED USA

TECHNICAL DATA NOT CLASSIFIED UNDER EXPORT CONTROL REGULATION

373 US Highway 46W Fairfield, NJ 07004, USA Phone +1 973.882.0211

info@lynred-usa.com

NIT (New Imaging Technologies) Premium SWIR by LYNRED

1 impasse de la Noisette 91370 Verrières-le-Buisson - France

info@new-imaging-technologies.com

2025@LYNRED. Photos: THALES & LYNRED.-Printed in France. Oct 2025. Technical characteristics described in this data sheet are for information only. Th