



LYNRED®

See Beyond Horizons



**THERMAL
SENSORS
TECHNOLOGIES
FOR DISMOUNTED
SOLDIER**

ON THE OPERATION FIELD


The soldier's equipment is a subject of major importance. Today, it benefits from the latest innovations, especially in the field of thermal imaging.

The latest developments in thermal imaging sensors contribute to improving their survival conditions and their performance by extending their autonomy, their intelligence and intervention capacity but also by participating in tactical choices whatever the conditions.

To support them in these missions, LYNRED offers a wide range of cooled and uncooled thermal detectors covering the infrared spectrum.



RELIABILITY



HIGH
RESOLUTION



IMAGE
QUALITY



RUGGEDIZED
FOR HARSH
ENVIRONMENTS

Soldier's equipment:

- BINOCULARS
- MONOCULARS
- CLIP-ON HELMET
- RIFLE SIGHT ...

Use cases:

- FIELD RECONNAISSANCE
- TARGET ACQUISITION
- BORDER CONTROL
- SITUATION AWARENESS



CHALLENGES

Thermal imaging meets the needs of the soldier to see beyond the visible by extending his operational capabilities by day and night; and this in all operational environments (dust, fire...).

The natural defogging properties of infrared technologies support the soldier's decision making in the field of operations.

The key factors necessary for these missions are :

- **IMAGE FLUIDITY**
- **EASE OF USE**
- **COMPATIBILITY OF THE EQUIPMENT WITH THE SOLDIER'S MOBILITY**



Thermal imaging must be incorporated into the soldier's ecosystem and facilitate the analysis of information collected by other sensors (acoustic, laser, radio frequency)




LYNRED: the partner you can rely on

- **High-performance infrared detectors for more than 30 years** (high sensitivity, high frame rate...). Our products provide a tactical advantage through their unmatched detection, recognition and target identification capabilities, helping to protect lives
- **An extensive range of cooled and uncooled thermal detectors** covering the entire infrared spectrum to support infantry troops with their missions
- **Reliable products** approved for use in harsh environments (MIL-STD-810/833, Thermal weapon sight) and guaranteed long-term availability compatible with military programs
- **A dedicated customer support** tasked with providing assistance and technical support. We take a proactive approach to responding to your questions and needs. Our engineers have the skills to work efficiently with your people, from R&D to engineering. Our customer support are fully integrated into our product lineup, personalized, and available to all customers. Our mission is to help boost your technical capabilities to make your infrared solution development processes more efficient and shorten time to market
- **Independent supplier** located in Europe

LYNRED infrared detectors
bring your thermal systems to life



3 millions detectors
delivered since 2016



UNCOOLED FOR SHORT TO MEDIUM RANGE  Clip-on to helmets, monoculars and TWS	PRODUCT	FORMAT & PIXEL PITCH	SPECTRAL BAND	NETD	POWER CONSUMPTION		WEIGHT	SIZE (TYPE PACKAGING)
					DIGITAL OUTPUT MODE	ANALOG OUTPUT MODE		
	ATTO640D-04™	VGA, 640 x 480 , 12µm	8 - 14µm	< 50mK (f/1, 300K, 30Hz)	< 320mW @ 60Hz	< 150mW @ 60Hz < 140mW @ 30Hz	< 3g	17.3 x 17.3 x 4.9 mm ³ (Wafer level packaging)
	ATTO1024-02™	XGA, 1024 x 768, 12µm	8 - 14µm	< 50mK (f/1, 300K, 30Hz)	-	≤ 470mW @ 50Hz (2 outputs) ≤ 550mW @ 100Hz (4 outputs)	< 10g	29.5 x 29.5 x 5.6 mm ³ (Ceramics)
	ATTO1280-02™	SXGA, 1280 x 1024, 12µm	8 - 14µm	< 50mK (f/1, 300K, 30Hz)	-	≤ 470mW @ 30Hz (2 outputs) ≤ 550mW @ 60Hz (4 outputs)	< 10g	29.5 x 29.5 x 5.6 mm ³ (Ceramics)
	PICO640S™	VGA, 640 x 480 , 17µm	8 - 14µm	< 30mK (f/1, 300K, 30Hz)	-	< 130mW	< 6.5g	24.4 x 24.4 x 4.7 mm ³ (Ceramic)
	YOCTO1024™	XGA, 1024 x 768, 8.5µm	8 - 14µm	< 50mK (f/1, 300K, 30Hz)	-	< 260mW	< 4g	< 18 x 18 x 4.85 mm ³ (Ceramic)
	ATI640™	VGA, 640 x 480 , 12µm	8 - 14µm	< 24mK (f/1, 300K, 60Hz, Denoising)	< 1W	-	15g(Core)	24.6 x 24.6 x 19mm (Core)

COOLED FOR HIGH PERFORMANCE & LONG RANGE  Multifunction binoculars	PRODUCT	FORMAT & PIXEL PITCH	SPECTRAL BAND	TYPICAL NETD*	POWER CONSUMPTION		WEIGHT	SIZE	CDT@20°C
					REGULATED INPUT POWER	COOLDOWN INPUT POWER			
	GALATEA MW™	VGA, 640 x 512, 15µm	3.6-4.2µm	<25mK (f/4, 300K, 60Hz, 50% WF)	< 2Wdc	< 6.9Wdc	230g	96 x 50 x 48mm (230cm ³)	180sec
	LEO MW™	VGA, 640 x 512, 15µm	3.7-4.8µm	20mK (f/5.5, 293K, 60Hz, 50% WF)	< 5.3Wdc	< 2.4Wdc	< 355g	121 x 73 x 58.5mm (516cm ³)	250sec
	ARGO MW SL™  Available in ATI ARGO MW SL™	640 x 512, 15µm	3.7 - 4.8µm	<33mK (300K, 50% WF, f/4, 25Hz)	< 3.8Wdc	< 12.0Wdc	360g	56 x 77.5 x 72mm	300sec
	SEEGNUS MW SL™ 	1280 x 1024, 7.5µm	3.6 - 4.2µm	42mK (300K, 50% WF, f/3, 25Hz)	< 3.7Wdc	< 13.5Wdc	360g	56 x 77.5 x 72mm	<280sec

*Typical value done with standardized LYNRED setup



40^{years}

of experience

80%

exports

1,000

Qualified
workforce

15%

revenue
invested in R&D

***LYNRED, global infrared industry
leader offering a very large
products portfolio.***

- LYNRED, an european leader
in sovereign critical technologies
at the heart of strategic rearmament
- LYNRED, a dependable partner of choice
creating infrared solutions for a safer world

**LYNRED HEADQUARTERS
DEVELOPMENT & PRODUCTION CENTER**

Actipole - CS 10021
364, route de Valence
38113 Veurey-Voroize, France

Phone +33 (0)4 76 28 77 00
info@lynred.com



www.lynred.com

LYNRED USA

373 US Highway 46W
Fairfield, NJ 07004, USA
Phone +1 973.882.0211
info@lynred-usa.com



www.lynred-usa.com

**NIT (NEW IMAGING TECHNOLOGIES)
PREMIUM SWIR BY LYNRED**

1 impasse de la Noisette
91370 Verrières-le-Buisson, France
Phone +33 (0)1 64 47 88 58
info@new-imaging-technologies.com



www.new-imaging-technologies.com